

## Astra tiles

|                            |                                        |                                                        |
|----------------------------|----------------------------------------|--------------------------------------------------------|
| <b>Tuft gauge</b>          | 1/10 loop pile                         | ISO 2424                                               |
| <b>Pilecomposition</b>     | 100% PP                                | ISO 2424                                               |
| <b>Primary Backing</b>     | Non Woven                              | ISO 2424                                               |
| <b>Secondary backing</b>   | Bitumen                                | ISO 2424                                               |
| <b>Width</b>               | 50x50 cm ± 0.2%                        | EN 984                                                 |
| <b>Pile Weight</b>         | 400 gr/m <sup>2</sup>                  | ISO 8543                                               |
| <b>Total weight</b>        | Bitumen : 3790 gr/m <sup>2</sup> ± 15% | ISO 8543                                               |
| <b>Pile height</b>         | 3 mm ± 2 mm                            | ISO 1766                                               |
| <b>Total Height</b>        | Bitumen : 5 mm                         | ISO 1765                                               |
| <b>Number of knots</b>     | 168.000 /m <sup>2</sup> -7.5% .+10%    | ISO 1763                                               |
| <b>Fire Classification</b> | Cfl-S1                                 | EN 13501-1                                             |
| <b>Use Area</b>            | Medium domestic use (22)               | EN 1307                                                |
| <b>GUT Nr.</b>             | 58CBAE2F                               | <a href="http://www.pro-dis.info">www.pro-dis.info</a> |
| <b>Light fastness</b>      | ≥ 5                                    | 105-B02                                                |
| <b>Wearebility</b>         | ≥ 4                                    | 105-X12                                                |
| <b>Water fastness</b>      | ≥ 4                                    | 105-E01                                                |

## Floorsymbols



## Certificates

