

Marmaris

Tuft gauge	1/10 loop pile	ISO 2424
Pilecomposition	100% PA SDN	ISO 2424
Primary Backing	Non Woven	ISO 2424
Secondary backing	Bitumen	ISO 2424
Width	50x50 cm ± 0,2%	EN 984
Pile Weight	690 gr/m ²	ISO 8543
Total weight	Bitumen : 4425 gr/m ² ± 15%	ISO 8543
Pile height	3 mm ± 2 mm	ISO 1766
Total Height	Bitumen : 6 mm	ISO 1765
Number of knots	240.379 /m ² -7.5% .+10%	ISO 1763
Fire Classification	Bfl-S1	EN 13501-1
Transversal resistance	Ω	ISO 10965
Use Area	Heavy project use (33)	EN 1307
Evaluated sound absorptions grade	0,15 αW αW	
Sound Insulation	ca. 25 dB	ISO 10140
Thermal resistance	ca. 0,0639 (0,639 TOG) M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC3	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates

