

Mustang tiles

Tuft gauge	1/10 loop pile	ISO 2424
Pilecomposition	100% PA SDN	ISO 2424
Primary Backing	Non Woven	ISO 2424
Secondary backing	Bitumen	ISO 2424
Width	50x50 cm ± 0,2%	EN 984
Pile Density	0,139 gr/cm ³	ISO 8543
Pile Weight	550 gr/m ²	ISO 8543
Total weight	Bitumen : 4300 gr/m ² ± 15%	ISO 8543
Pile height	3 mm ± 2 mm	ISO 1766
Total Height	Bitumen : 5 mm	ISO 1765
Number of knots	189.600 /m ² -7.5% .+10%	ISO 1763
Fire Classification	Bfl-S1	EN 13501-1
Transversal resistance	Ω	ISO 10965
Use Area	Heavy project use (33)	EN 1307
GUT Nr.	F7FCFD0C	www.pro-dis.info
Evaluated sound absorptions grade	Ca. 0,15 αW αW	
Sound Insulation	ca. 25 dB	ISO 10140
Thermal resistance	ca. 0,07 (0,7 TOG) M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC2	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates

 2018 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-022RBM236 Reaction to fire: Bfl-s1 Slip resistance: DS Resilient floor covering to be used within a building	 2018 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-022RBM236-UK Reaction to fire: Bfl-s1 Slip resistance: DS Resilient floor covering to be used within a building
---	--

