



# CE – Declaration of Conformity

Document: CE211123E\_Prelude LED  
 Product Inspection: PI200424A  
 Risk Assessment: RA200317A  
 Test report's: DEKRA 4380261.50, 4341689.50  
 140327070GZU-002 Intertek

We, **SG Produktion A/S**  
**Egestubben 16-26**  
**DK-5270 Odense N - Denmark**

declare under sole responsibility that the product

## Luminaire

\_\_\_\_\_  
 Type

**Prelude LED**

\_\_\_\_\_  
 Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

<i>Directive 2014 / 30 / EU</i>	<i>Directive 2014 / 35 / EU</i>	<i>Directive 2009 / 125 / EF</i>  (Regs 244/2009, 245/2009, 347/2010)*
Electromagnetic compatibility (EMC)	Low Voltage directive (LVD)	Ecodesign requirements (ECO) * As applicable and including amendments

*RoHS 2011 / 65 / EU + RoHS III / EU 2015/863*

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

- EN 60598-1:2015 + A1:2018** (Luminaires - General requirements)
- EN 60598-2-1:2018** (Luminaires – General purpose)
- EN 62493:2015** (EMF – Lighting equipment related to human exposure)
- EN 55015:2019 + A11:2020** (EMC - Radio disturbance)
- EN 61000-3-2:2019** (EMC - Harmonics)
- EN 61000-3-3:2013 + A1:2019** (EMC – Voltage change, fluctuation & flicker)
- EN 61547:2009** (EMC - Immunity)

CE Marking date: 2021

Statement of Conformity

issued by SG Produktion A/S

### Manufacturer

Odense, 23/11-2021  
 Place and date of issue

Martin Etrup

Name of authorized person

Signature of authorized person

Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
7021981113407	Prelude Hvit 1000lm	2700K Ra>90 Faseavsnitt	701400
7021981113452	Prelude Hvit 1070lm	3000K Ra>90 Faseavsnitt	701400
7021981113469	Prelude Hvit m/ kontakt 1070lm	3000K Ra>90 Faseavsnitt	701400
7021981113438	Prelude Hvit m/ 2 x kontakt 1000lm	2700K Ra>90 Faseavsnitt	701400
7021981973407	Prelude Børstet stål 900lm	2700K Ra>90 Faseavsnitt	701400
7021981113414	Prelude Hvit m/ kontakt 1000lm	2700K Ra>90 Faseavsnitt	701400
7021981973414	Prelude Børstet stål m/ kontakt 900lm	2700K Ra>90 Faseavsnitt	701400
7021981113537	Prelude Hvit	3000K	701400
7021981113520	Prelude Hvit	3000K Ra>80 Ikke dimbar	701400
7021981983246	Prelude Krom	2700K Ra>80 Ikke dimbar	701400
7021981113247	Prelude Hvit	2700K Ra>80 Ikke dimbar	701400
7021981973452	Prelude Børstet stål 960lm	3000K Ra>90 Faseavsnitt	701400
7021981973476	Prelude Børstet stål 960lm	3000K Ra>90	701400
7021981113421	Prelude Hvit m/ kontakt 1000lm	2700K Ra>90 Faseavsnitt	701400
7021981113476	Prelude Hvit m/ kontakt 1070lm	3000K Ra>90 Faseavsnitt	701400
7021981113483	Prelude Hvit m/ 2 x kontakt 1070lm	3000K Ra>90 Faseavsnitt	701400
7021981973469	Prelude Børstet stål m/ kontakt 960lm	3000K Ra>90 Faseavsnitt	701400
7021981113445	Prelude Hvit m/ 2 x kontakt 1000lm	2700K Ra>90 Faseavsnitt	701400
7021981113490	Prelude Hvit m/ 2 x kontakt 1070lm	3000K Ra>90 Faseavsnitt	701400

