



DESIGNLIGHT

SCANDINAVIAN AB

DOWNLIGHT, TRACY

E-NR: 74 774 92

ART NR: D-20MW2CCTDA

EFFECT POWER	MATERIAL MATERIAL	KELVIN KELVIN	ARMATURFÄRG ARMATURE COLOR	ANSLUTNING CONNECTION	TOTAL LUMEN	USEFUL LUMEN
20W	ALUMINIUM/ PLASTIC	3000K/ 4000K	MATT WHITE	230V	2270LM @3000K	2035LM @3000K

CE, ROHS  

500MA
LED 1x16,5W
LIGHT SOURCE WATT




1083
CD



CRI: 80




IP40



LIFETIME
L70B50: 50.000H








- **UTBYTBAR LED-MODUL**
- **MÖJLIGHET ATT BYTA REFLEKTORFÄRG**
- **KOSTNADSEFFEKTIV ALLMÄNBELYSNING**

- **REPLACEABLE LED MODULE**
- **POSSIBILITY TO CHANGE THE REFLECTOR COLOR**
- **COST-EFFECTIVE LIGHTING**




SWITCHABLE
3000K
4000K

DALI 2



Mått/Dimension




1.900K	2.700-3.000K	4.000-4.500K	4.800K	5.000-5.000K	7.000-7.500K	10.000K
STEARINLJUS CANDLE	VARMT VIT WARM WHITE	NATURLIG VIT NATURAL WHITE	SOLLJUS DIRECT SUN	VITT DAGSLJUS DAY WHITE	KALLVIT COOL WHITE	BLÅ HIMMEL BLUE SKY


LÄS MER OM VÅRA GARANTIVILLKOR PÅ WWW.DESIGNLIGHT.NU

READ MORE ABOUT OUR WARRANTY CONDITIONS AT: WWW.DESIGNLIGHT.NU


1. Stäng av strömmen/
Turn off the power



2. Borra hål i taket/
Drill hole in ceiling



3. Anslut till LED-drivern/
Connect to LED driver



**PRODUKTEN INNEHÅLLER
 LJUSKÄLLA MED
 ENERGIMÄRKNING
 KLASSE E (3000K).
 KLASSE D (4000K).**

**THIS PRODUCT CONTAINS
 A LIGHT SOURCE OF
 ENERGY EFFICIENCY
 CLASS <E> (3000K).
 CLASS <D> (4000K).**

⚠ SÄKERHET:

1. Läs igenom hela manualen noggrant före installation.
2. Kontrollmät ALLTID diametern före håtagning i tak.
3. Försäkra dig om att spänningen är fränslagen före installation eller underhåll.
4. Installation ska utföras av behörig elektriker.
5. Ljuskällan är ej utbytbart. Hela armaturen måste bytas när ljuskällan är förbrukad.

⚠ SAFETY:

1. Read the entire manual carefully before installation.
2. ALWAYS check the diameter before drilling holes in the ceiling.
3. Make sure that the power is switched off before installation or maintenance.
4. Installation must be performed by a qualified electrician.
5. The light source of this luminaire is not replaceable, when the light source reaches its end of life the whole luminaire shall be replaced.

DESIGNLIGHT
 SCANDINAVIAN AB

DESIGNLIGHT SCANDINAVIAN AB · TOFFELVÄGEN 1 · SE-342 60 MOHEDA · SWEDEN
 TELEFON/PHONE +46 (0)472-716 10 · INFO@DESIGNLIGHT.NU · WWW.DESIGNLIGHT.NU