

Karakteristike proizvoda			
Format	2190 mm x 162 mm x 12 mm		
Habajući sloj	2,5 mm		
Pakovanje	Cuti 6 Buc.= 2,13 m ² /  21,17 kg		
Garancija prema SKANDOR garantnim uslovima			
Privatni sektor	30 godina		
Komercijalni sektor	15 godina		
Napomene	Preporučuje se upotreba komercijalno dostupne zaštitne podloge i filcanih klizača u skladu sa uputstvom.		
	Za čišćenje i održavanje, vidi uputstvo		
	Podložno tehničkim izmenama		
			
Klasifikacija			
		Standard za testiranje	Ocena
	Otpornost na požar	EN 13501-1	Dfl - s1
	Emisije formaldehida	EN 717-1	clasă E1
	Dinamički koeficijent trenja	USRV	R11
Karakteristike proizvoda			
	Površina	prirodno nauljena	
	Površinska struktura	četkana	
	Klik sistem	Fold-Down	
	Pogodan za podno grejanje toplom vodom	Da – Napomena: može se koristiti do 26°C	
	Toplotni otpor	R = 0,15 (m ² * K)/W	
	Zahtevi za podlogu	Privatni CS ≥ 10 kPa KomercijalniCS ≥ 60 kPa	
	Pogodan za vlažne prostorije	Ne	