



TIRANA

uplight

58909B

9007371471119

The elegant uplight in matt black and bronze metal with satin acrylic brings stylish light to your home. With an infinitely variable touch dimmer, you can adjust the brightness of the floodlight to your liking and fix the color. The memory function saves your preferred settings for your next use. The uplight is movable and can be rotated or swivelled to adjust the light individually. With dimensions of 800x405x1830mm and a cable length of 1800mm, it fits perfectly into any room. In addition, the uplight has a reading light with a diameter of 12 cm. It comes with LED bulbs: 40W with 4000lm source and 2800lm output and 5.5W with 570lm source and 400lm output, adjustable between 2700-6000K. Order this versatile uplight today and experience comfortable and atmospheric light in your home.

technical data:

uplight metal black matt, metal bronze colored matt, acrylic satined, cable PVC black, Touch On/Off, Dimmable, Continuous Touch Dimmer, Color fixing, Moveable, Rotatable / Swiveling, LxWxH: 800x405x1830mm, cable length 1800mm, incl. LED 40W 230V, 400-4000lm Source, 280-2800lm Output, CCT 2700/4000/6000K, incl. LED 5.5W 230V, 57-570lm Source, 40-400lm Output, CCT 2700/4000/6000K

Socket 1:

Light source incl.:	Yes
Amount:	1
Fitting:	LED
Power:	40,00 Watt
Voltage:	230,00 Volt
Lumen output max.:	2800 Lumen
Lumensource max.:	4000 Lumen
Color Temperature:	
CCT:	2700 Kelvin-4000 Kelvin-6000 K
Lifetime:	20000 h
Number of switching Cycles:	10000 x
Colour Rendering:	80 Ra
Angle of radiation:	120 °
EEK:	F
Recommended light source:	

Socket 2:

Light source incl.:	Yes
Amount:	1
Fitting:	LED
Power:	5,50 Watt
Voltage:	230,00 Volt
Lumen output max.:	400 Lumen
Lumensource max.:	570 Lumen
Color Temperature:	
CCT:	2700 Kelvin-4000 Kelvin-6000 K
EEK:	F
Recommended light source:	

Characteristics:

Height:	1830 mm
Width:	405 mm
Length:	800 mm
Diameter:	
Overhang:	
Material:	metal; acrylic; metal; ; ; acrylic
Colour:	black matt; satined; bronze colored matt; ; ;
Protection Class:	2
Degree of Protection:	IP20

Packaging details:

Packing unit:	1 pcs.
Measurements single box (LxWxH):	440x95x1040 mm
Measurements master box (LxWxH):	440x95x1040 mm
Netweight product:	9,49 kg
Grossweight single box:	10,9 kg